

qineo

QINEO Pulse C



QINEO Pulse C – more power for pulsed arc welding

MIG/MAG Pulsed arc welding power source with integrated wire drive unit

CLOOS

Weld your way.

qineo

QINEO Pulse C

350 A
60%
duty cycle

450 A
60%
duty cycle

600 A
60%
duty cycle



QINEO Pulse – more power for pulsed arc welding

Variety and precision: these are the crucial conditions for successful pulsed arc welding. Whatever the capacity class. 350 A, 450 A or 600 A: Each QINEO Pulse offers seven different welding processes for a large variety of applications. The QINEO Pulse is equipped with a synergy mode and two fine adjustments. The synergic characteristic curves can therefore be perfectly adapted to external factors.

- **Powerful and versatile:** Three capacity classes with seven different welding processes
- **Precision by technology:** Two independent fine adjustments for the perfect arc
- **Compensation** of the external circuit influences
- **Best quality:** Optimum ignition and welding characteristics
- **Flexibility:** Operating panel in power source or remote control according to requirement



MasterPlus operating module

Manual welding in perfection

- Intuitive operation
- Job favourites
- Memory for 4 welding circuits



Premium operating module

Sophisticated automation

- Intuitive operation
- Diagnostic functions
- Memory for 4 welding circuits

	Pulse 350 C	Pulse 450 C	Pulse 600 C
Welding current	40 A - 350 A	40 A - 450 A	40 A - 600 A
Welding current at 60 % duty cycle	350 A / 31.5 V	450 A / 36.5 V	600 A / 44 V
Welding current at 100 % duty cycle	270 A / 27.5 V	350 A / 31.5 V	465 A / 37.5 V
Open circuit voltage	75 V	75 V	87 V
Mains voltage	400 V / 50 Hz / 3 phases	400 V / 50 Hz / 3 phases	400 V / 50 Hz / 3 phases
Special voltages	380 V / 415 V / 440 V / 480 V / 500 V	380 V / 415 V / 440 V / 480 V / 500 V	380 V / 415 V / 440 V / 480 V / 500 V
Connection cable	4 x 4 mm ²	4 x 6 mm ²	4 x 10 mm ²
Mains protection	25 A	32 A	50 A
Type of protection	IP 23	IP 23	IP 23
Insulating class	F	F	F
Type of cooling	F	F	F
Dimensions (L/W/H) compact unit	1226 x 630 x 942 mm	1226 x 630 x 942 mm	1226 x 630 x 942 mm
Weight compact unit	181 kg	194 kg	234 kg
Maximum track width	approx. 552 mm	approx. 552 mm	approx. 552 mm
Operating modes	2-cycles, 4-cycles, Super 4 -cycles, spot welding/interval, external start (with operating modules MASTER PLUS and PREMIUM)		

All over the world!



Carl Cloos Schweisstechnik GmbH
Main office: Carl-Cloos-Strasse 1
Central warehouse: Carl-Cloos-Strasse 6
35708 Haiger
GERMANY

Tel.: +49 (0)2773 85-0
Fax: +49 (0)2773 85-275
E-Mail info@cloos.de

CLOOS

Weld your way.